

Sub. a²

I claim:

1. An injection molded dome-cap sensor and circuitry comprising;
an injection molded flexible dome-cap depressible
5 against
pressure-sensitive variable-conductance material
positioned for providing an analog variably conductive
path between
circuit elements located on
10 a circuit board, said circuit elements at least part
of
analog-to-digital conversion circuitry for
outputting digital information representing at least three
levels of electrical resistance of said material.
- 15 2. An injection molded dome-cap sensor and circuitry
in accordance with claim 1 wherein said conversion
circuitry is structured for reading any one of at least
nine readable levels of electrical resistance of said
material.
- 20 3. An injection molded dome-cap sensor and circuitry
in accordance with claim 1 wherein said conversion
circuitry is structured for reading any one of at least
129 readable levels of electrical resistance of said
25 material.
4. An injection molded dome-cap sensor and circuitry
according to claim 1 wherein said material is carried by
said dome-cap.
5. An injection molded dome-cap sensor and circuitry
30 according to claim 3 wherein said dome-cap is made of
thermoset rubber.

05599095-052100

6. An injection molded dome-cap sensor and circuitry according to claim 4 wherein said dome-cap is structured to produce a user discernable tactile feedback upon depression of the dome-cap.

5 7. An injection molded dome-cap sensor and circuitry comprising;

an injection molded flexible dome-cap depressible against

an active element of pressure-sensitive variable-conductance material positioned for providing a variably conductive path between

circuit elements located on

a circuit board, said circuit elements at least part of

15 circuitry structured for reading at least three levels of conductivity of said active element.

8. An injection molded dome-cap sensor and circuitry in accordance with claim 7 wherein said circuitry is structured for reading any one of at least nine readable levels of conductivity of said injection molded flexible dome-cap sensor.

9. An injection molded dome-cap sensor and circuitry in accordance with claim 7 wherein said circuitry is structured for reading any one of at least 129 readable levels of conductivity of said injection molded flexible dome-cap sensor.

10. An injection molded dome-cap sensor and circuitry according to claim 7 wherein said material is carried by said dome-cap.

09599095-062100

11. An injection molded dome-cap sensor and circuitry according to claim 8 wherein said dome-cap is structured to produce a user discernable tactile feedback upon depression of the dome-cap.

5 12. An injection molded dome-cap sensor and circuitry according to claim 11 wherein said dome-cap is made of thermoset rubber.

13. An elastomeric dome-cap sensor and circuitry comprising;
10 an injection molded dome-cap made of thermoset rubber and structured to be depressible against pressure-sensitive variable-conductance material carried by said dome-cap, said material positioned for providing an analog variably conductive path between
15 circuit elements located on a circuit board, said circuit elements at least part of
analog-to-digital conversion circuitry for outputting digital information representing at least 9 readable
20 levels of electrical resistance of said material;
said dome-cap is structured to produce a user discernable tactile feedback upon depression of the dome-cap.

14. An improved analog sensing circuit of the type
25 including a user manipulable variable-conductance sensor and circuitry for reading said sensor;
wherein the improvement comprises:
the variable-conductance sensor is an injection molded flexible dome-cap positioned over a pressure-sensitive
30 variable-conductance material.

15. An improved analog sensing circuit in accordance with claim 14 wherein said pressure-sensitive

005005-05100

variable-conductance material is positioned within said injection molded flexible dome-cap.

16. An improved analog sensing circuit in accordance
5 with claim 14 wherein said injection molded flexible dome-cap carries said pressure-sensitive variable-conductance material.

17. An improved analog sensing circuit in accordance
10 with claim 14 wherein said injection molded flexible dome-cap is made primarily of polymer flexible material.

18. An improved analog sensing circuit in accordance
15 with claim 14 wherein said injection molded dome-cap produces a user discernable tactile feedback upon depressive pressure being applied to the dome-cap.

19. An improved method for using an injection molded
20 flexible dome-cap sensor of the type wherein an injection molded flexible dome-cap is capable of depressing an active element which is part of an electronic circuit, said injection molded flexible dome-cap depressible for transferring force into said active element, said electronic circuit structured for reading the active
25 element as being in any one of a plurality of states;

wherein the improvement comprises the steps of:

a) depressing variably said injection molded flexible dome-cap;

b) reading said active element as being in any one of
30 at least seventeen readable states;

c) outputting, as digital information, a read state of said active element, said outputting capable of producing as digital information at least seventeen different digital values that correspond to at least
35 seventeen different read states of said active element.

00500005-062100

20. An improved method for outputting a read state of an injection molded flexible dome-cap sensor of the type wherein an active element is positioned with an injection molded flexible dome-cap which is positioned as
5 part of an electronic circuit, said injection molded flexible dome-cap depressible for transferring force into said active element, said electronic circuit structured for reading said active element as being in any one of a plurality of states, and outputting a read state as
10 digital information, said outputting of the read state requiring one digital bit;

wherein the improvement comprises the step:

outputting, as digital information, a read state of said active element, said outputting requiring at least
15 four digital bits.

0055095-062100